



# SAFETY DATA SHEET: ENGINE OIL FLUSH PRO

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product Identifier

#### **Trade Name**

Engine Oil Flush Pro

#### Product no.

DC345

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### ▼ Relevant identified uses of the substance or mixture

۸dditive

Restricted to professional users.

#### Uses advised against

None known.

## 1.3. Details of the supplier of the safety data sheet

#### Company and address

#### **DC Lubricants Limited**

7 The Old Mill, Reading Road

Pangbourne

Reading, RG8 7HY, UK

+44 118 304 8449

https://dclubricants.uk/

# **Contact person**

**Product Safety Department** 

#### E-mail

hello@dclubricants.uk

#### Revision

11/10/2023 SDS Version

5.0

## Date of previous version

03/03/2023 (4.0)

## **Emergency telephone number**

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures"

# SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

## 2.2. Label elements

## Hazard pictogram(s)

Not applicable.

## Signal word

Not applicable

# Hazard statement(s)

Not applicable

ENGINEOILFLUSHPRO Page 1 of 11



## Precautionary statement(s)

General

.

Prevention

-

Response

\_

Storage

-

Disposal

...

#### Hazardous substances

None known.

## Additional labelling

EUH208, Contains Phenol, C14-18-alkyl derivs. May produce an allergic reaction. EUH210, Safety data sheet available on request.

#### 2.3. Other hazards

#### **Additional warnings**

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

# SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable. This product is a mixture.

#### 3.2. ▼Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]	CAS No.: 64742-65-0 EC No.: 265-169-7 UK-REACH: Index No.: 649-474-00-6	75-100%	Asp. Tox. 1, H304	[12], [19]
Phenol, C14-18-alkyl derivs.	CAS No.: 1190625-94-5 EC No.: 931-468-2 UK-REACH: Index No.:	<0.25%	Skin Sens. 1B, H317 STOT RE 2, H373	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

[12] The classification as a carcinogen will not be taken into account as the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method' (CLP, Annex VI, note L). [19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

ENGINEOILFLUSHPRO Page 2 of 11





#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

## **General Information**

In the case of accident: Contact a doctor or casualty department - take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### **Inhalation**

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention

#### **▼**Eve contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

#### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

#### Burns

Not applicable.

#### 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

## 4.3. ▼ Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# Information to medics

Bring this safety data sheet or the label from this product.

# SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2 Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

#### 5.3 Advice for firefighters

Fire fighters should wear appropriate personal protective equipment.

#### SECTION 6: Accidental release measures

#### 6.1 ▼ Personal precautions, protective equipment and emergency procedures

Contaminated areas may be slippery.

## 6.2 Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

#### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

ENGINEOILFLUSHPRO Page 3 of 11



## 6.4 Reference to other sections

See section 13 "Disposal considerations" on handling of waste. See section 8 "Exposure controls/personal protection" for protective measures

## SECTION 7: Handling and storage

## 7.1 Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

#### 7.2 Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Recommended storage material

Always store in containers of the same material as the original container.

#### Storage temperature

Dry, cool and well ventilated

<40°C.

#### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 7.3 Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

No substances are listed in the national list of substances with an occupational exposure limit.

#### **▼ DNEL**

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100  $^{\circ}$ F (19cSt at 40  $^{\circ}$ C).]

Duration:	Route of exposure:	DNEL:
Long term - Systemic effects - Workers	Dermal	970 µg/kgbw/day
Long term - Local effects - General population	Inhalation	1.19 mg/m³
Long term - Local effects - Workers	Inhalation	5.58 mg/m³
Long term - Systemic effects - Workers	Inhalation	2.73 mg/m³
Long term - Systemic effects - General population	Oral	740 µg/kgbw/day

#### Phenol, C14-18-alkyl derivs

Du	ration:	Route of exposure:	DNEL:
Lor	ng term - Systemic effects - Workers	Dermal	300 µg/kgbw/day
Lor	ng term - Systemic effects - Workers	Inhalation	1.17 mg/m³

#### ▼ PNEC

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]

Route of exposure:	Duration of exposure:	PNEC:
Predators		9.33 mg/kg

# Phenol, C14-18-alkyl derivs

Route of exposure:	Duration of exposure:	PNEC:
Freshwater		100 μg/L
Freshwater sediment		4266.16 mg/kg
Intermittent release (freshwater)		1 mg/L

ENGINEOILFLUSHPRO Page 4 of 11



Route of exposure:	Duration of exposure:	PNEC:
Marine water		10 μg/L
Marine water sediment		426.62 mg/kg
Predators		3.3 mg/kg
Sewage treatment plant		100 mg/L
Soil		852.58 mg/kg

#### 8.2 Exposure controls

Control is unnecessary if the product is used as intended.

#### **General recommendations**

Smoking, drinking and consumption of food is not allowed in the work area.

#### **Exposure scenarios**

There are no exposure scenarios implemented for this product.

#### **Exposure limits**

Occupational exposure limits have not been defined for the substances in this product.

#### Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of vapours.

#### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

#### Measures to avoid environmental exposure

No specific requirements.

## Individual protection measures, such as personal protective equipment

#### Generally

Use only UKCA marked protective equipment.

#### **Respiratory Equipment**

No specific requirements

#### **Skin protection**

No specific requirements.

#### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.65	> 240	EN374-2, EN374-3, EN388	
Vinyl/PVC	>0.35	>480	EN374-3, EN388	

## Eye protection

No specific requirements.

# SECTION 9: Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

Physical state

Liquid

Colour

Tan

#### Odour / Odour threshold

Characteristic

рŀ

Not applicable

Density (g/cm³)

0.873 (15 °C)

ENGINEOILFLUSHPRO Page 5 of 11



#### Kinematic viscosity

32.2 mm<sup>2</sup>/s (40 °C).

#### Particle characteristics

Not applicable - product is a liquid

#### Phase changes

#### Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

#### Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

#### Boiling point (°C)

No data available

#### Vapour pressure

No data available

#### Relative vapour density

No data available

## Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

#### Data on fire and explosion hazards

#### Flash point (°C)

>200

#### Flammability (°C)

Testing not relevant or not possible due to the nature of the product.

## Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

## Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

#### Solubility

## Solubility in water

Insoluble

#### n-octanol/water coefficient

No data available

#### Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

## 9.2 Other information

## Evaporation rate (n-butylacetate = 100)

No data available

## Other physical and chemical parameters

No data available.

## **▼**Oxidizing properties

No data available

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

#### 10.3. Possibility of hazardous reactions

None known.

## 10.4. Conditions to avoid

None known.

#### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.





## SECTION 11: Toxicological information

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Product/substance  Species: Route of exposure: Test: Result:	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]  Rat Oral LD50 >5000 mg/kgbw
Product/substance  Species: Route of exposure: Test: Result:	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C) Rabbit Dermal LD50 >5000 mg/kg
Product/substance : Species: Route of exposure: Test: Result:	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]  Rat Inhalation LC50 >5.53 mg/l/4h

## Skin corrosion/irritation

Based on available data, the classification criteria are not met.

# Serious eye damage/irritation

Based on available data, the classification criteria are not met.

## **Respiratory sensitisation**

Based on available data, the classification criteria are not met.

## Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

## Carcinogenicity

Based on available data, the classification criteria are not met.

## Reproductive toxicity

Based on available data, the classification criteria are not met.

#### **STOT-single exposure**

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Product/substance	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Species:	Rat
Route of exposure:	Oral
Duration:	90 days
Test:	LOAEL
Result:	125 mg/kgbw
Conclusion	No adverse effect observed

ENGINEOILFLUSHPRO Page 7 of 11



Product/substance	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]
Species:	Rat
Route of exposure:	Dermal
Duration:	90 days
Test:	NOAEL
Result:	1000 mg/kgbw
Conclusion	No adverse effect observed

#### **Aspiration hazard**

Product/substance	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination
	of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent
	crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the
	range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F
	(19cSt at 40 °C).]
Kin. viscocity (mm²/s):	32.2
Conclusion	Aspiration hazard not applicable

#### 11.2. Information on other hazards

Long term effects

None known.

▼Endocrine disrupting properties

This mixture/product does not contain any substances considered to have hormone-disrupting properties in relation to health.

Other information

None known.

# SECTION 12: Ecological information

# 12.1. Toxicity

Product/substance  Species: Test: Result:	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]  Fish, Pimephales promelas  LC50  >100 mg/L
Product/substance  Species: Test: Result:	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]  Crustacean, Daphnia magna EC50 >10000 mg/L
Product/substance  Species: Test: Result:	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]  Fish, Oncorhynchus mykiss  NOEC  1000 mg/L
Product/substance  Species: Test: Result:	Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] Crustacean, Daphnia magna NOEC 10 mg/L

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878



Product/substance Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination

of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the

range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F

(19cSt at 40 °C).]

Species: Algae, Pseudokirchneriella subcapitata

Test: NOEC >100 mg/L

### 12.2. Persistence and degradability

Product/substance Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination

of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F

(19cSt at 40 °C).]

Biodegradable: No

Test Method: OECD 301 F Result: 31% 28d

#### 12.3. Bioaccumulative potential

Product/substance Distillates (petroleum), solvent-dewaxed heavy paraffinic;Baseoil - unspecified;[A complex combination

of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the

range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F

(19cSt at 40 °C).]
Potential bioaccumulation: No data available

LogPow: 9.2
BCF: 260

# 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

#### 12.6. ▼Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

# 12.7. Other adverse effects

None known.

# SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

#### **EWC** code

Not applicable.

## Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

# SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

<sup>\*</sup> Packing group

ENGINEOILFLUSHPRO Page 9 of 11

<sup>\*\*</sup> Environmental hazards





#### Additional information

Not dangerous goods according to ADR, IATA and IMDG.

## 14.6. Special precautions for user

Not applicable.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Restrictions for application**

Restricted to professional users.

## Demands for specific education

No specific requirements.

#### **SEVESO** - Categories / dangerous substances

Not applicable.

#### Additional information

Not applicable.

#### ▼ Sources

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

## 15.2. Chemical safety assessment

No

#### SECTION 16: Other information

# Full text of H-phrases as mentioned in section 3

H304, May be fatal if swallowed and enters airways.

H317, May cause an allergic skin reaction.

H373, May cause damage to organs through prolonged or repeated exposure.

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

ENGINEOILFLUSHPRO Page 10 of 11



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878



PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

**UN = United Nations** 

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

## Additional information

Not applicable.

#### ▼The safety data sheet is validated by

**Product Safety Department** 

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en

ENGINEOILFLUSHPRO Page 11 of 11