SAFETY DATA SHEET: Diesel Detox Pro Diesel

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1.Product identifier

Trade name
Emissions Detox Pro Diesel

Product no.
DC200

Unique formula identifier (UFI)
X2J0-201G-U00U-QK0T

1.2.Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture
A dditive

Use descriptors (REACH)

Product category	Description
	Additives to diesel fuel

Uses advised against
None known.

1.3.Details of the supplier of the safety data sheet

Company and address
DC Lubricants Limited
7 The Old Mill, Reading Road
Pangbourne
Reading, RG8 7HY, UK
+44 118 304 8449
https://dclubricants.uk/

Contact person
Product Safety Department

E-mail
hello@dclubricants.uk

Revision
11/07/2026

SDS Version
6.0

Date of previous version
11/10/2023 (5.0)

1.4.▼Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)
General public:
England - Dial 111 to reach NHS 111 (24 hour service)
Scotland - Dial 111 to reach NHS 24 (24 hour service)
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)
See section 4 “First aid measures”.

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1.Classification of the substance or mixture

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.
Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

2.2.Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

May be fatal if swallowed and enters airways. (H304)
Toxic to aquatic life with long lasting effects. (H411)

Precautionary statement(s)

General

Keep out of reach of children. (P102)

Prevention

Avoid release to the environment. (P273)

Re s pons e

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)
Do NOT induce vomiting. (P331)
Collect spillage. (P391)

▼Storage

Not applicable.

▼Disposal

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.

UFI: X2J0-201G-U00U-QK0T

2.3.Other hazards

▼Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. ▼Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics,	CAS No.: 64742-48-9 EC No.: 918-481-9	80-95%	EUH066 Asp. Tox. 1, H304	[15] , [19]

<2% aromatics	UK-REACH: Index No.:			
2-ethylhexyl nitrate	CAS No.: 27247-96-7 EC No.: 248-363-6 UK-REACH: Index No.:	5-10%	EUH044 EUH066 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS No.: 64742-47-8 EC No.: 926-141-6 UK-REACH: Index No.:	1-3%	EUH066 Asp. Tox. 1, H304	[19]
2-et h y l h ex an -1-o l	CAS No.: 104-76-7 EC No.: 203-234-3 UK-REACH: Index No.:	<1%	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

▼Other information

[1]European occupational exposure limit.
[15]The classification as a carcinogen / mutagen will not be taken into account as the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7) (CLP, Annex VI, note P).
[19]UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1.Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.
If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER/doctor.
Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Not applicable.

4.2.Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

4.3.Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:
Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1.Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2.Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Nitrogen oxides (NO_x)
Carbon oxides (CO / CO2)

5.3. ▾ Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1.Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Contaminated areas may be slippery.

6.2.Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3.Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4.Reference to other sections

See section 13 “Disposal considerations” on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1.Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.
Avoid direct contact with the product.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2.Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Keep only in original packaging.

Storage conditions

Dry, cool and well ventilated
Store out of direct sunlight.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3.Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1.Control parameters

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Long term exposure limit (8 hours) (ppm): 184
Long term exposure limit (8 hours) (mg/m³): 1200

2-ethylhexan-1-ol
Long term exposure limit (8 hours) (ppm): 1
Long term exposure limit (8 hours) (mg/m³): 5,4

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼DNEL

2-ethylhexan-1-ol

Duration:	Route of exposure:	DN EL:
Long term – Systemic effects - General population	Dermal	11.4 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	23 mg/kg bw/day
Long term – Local effects - General population	Inhalation	26.6 mg/m³
Long term – Local effects - Workers	Inhalation	53.2 mg/m³
Long term – Systemic effects - General population	Inhalation	2.3 mg/m³
Long term – Systemic effects - Workers	Inhalation	12.8 mg/m³
Short term – Local effects - General population	Inhalation	26.6 mg/m³
Short term – Local effects - Workers	Inhalation	53.2 mg/m³
Long term – Systemic effects - General population	Oral	1.1 mg/kg bw/day

2-ethylhexyl nitrate

Duration:	Route of exposure:	DN EL:
Long term – Local effects - General population	Dermal	22 µg/cm²
Long term – Local effects - Workers	Dermal	44 µg/cm²
Long term – Systemic effects - General population	Dermal	520 µg/kg bw/day
Long term – Systemic effects - Workers	Dermal	1 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	87 µg/m³
Long term – Systemic effects - Workers	Inhalation	350 µg/m³
Long term – Systemic effects - General population	Oral	25 µg/kg bw/day

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Duration:	Route of exposure:	DN EL:

Long term – Local effects - General population	Inhalation	178.57 mg/m³
Long term – Local effects - Workers	Inhalation	837.5 mg/m³
Long term – Systemic effects - General population	Inhalation	410 µg/m³
Long term – Systemic effects - Workers	Inhalation	1.9 mg/m³
Short term – Local effects - General population	Inhalation	640 mg/m³
Short term – Local effects - Workers	Inhalation	1066.67 mg/m³
Short term – Systemic effects - General population	Inhalation	1152 mg/m³
Short term – Systemic effects - Workers	Inhalation	1286.4 mg/m³

PNEC

2-ethylhexan-1-ol

Route of exposure:	**Duration of Exposure:**	**PNEC:**
F resh wat er		17 µg/L
Freshwater sediment		284 µg/kg
Intermittent release (freshwater)		170 µg/L
Marine water		1.7 µg/L
Marine water sediment		28.4 µg/kg
P red ato rs		55 mg/kg
Sewage treatment plant		10 mg/L
Soil		47 µg/kg

2-ethylhexyl nitrate

Route of exposure:	**Duration of Exposure:**	**PNEC:**
F resh wat er		800 ng/L
Freshwater sediment		740 ng/kg
Marine water		80 ng/L
Marine water sediment		740 ng/kg
Sewage treatment plant		10 mg/L
Soil		191 ng/kg

8.2.Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.
Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
No special when used as intended.			

Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be wo rn .	-	-	

▼Hand protection

Material	Glove thickness (mm)	Breakthrough time (m in.)	Standards	
Nitrile	0,38	> 240	EN374-2, EN16523-1, EN388	

Eye protection

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: Physical and chemical properties

9.1.Information on basic physical and chemical properties

Physical state

Liquid

Colour

Pale yellow

Odour / Odour threshold

S olve nt

pH

No data available

Density (g/cm³)

0.8081 (20 °C)

▼Kinematic viscosity

No data available.

Particle characteristics

Not applicable - product is a liquid

Phase changes

Melting point/Freezing point (°C)

No data available

Softening point/range (°C)

Does not apply to liquids.

Boiling point (°C)

150-230

Vapour pressure
No data available

Relative vapour density
No data available

Decomposition temperature (°C)
No data available

Data on fire and explosion hazards

Flash point (°C)
>62

Flammability (°C)
>251

Auto-ignition temperature (°C)
No data available

Lower and upper explosion limit (% v/v)
Not applicable

S olubility

Solubility in water
Insoluble

n-octanol/water coefficient (LogKow)
No data available

Solubility in fat (g/L)
No data available

9.2.Other information

Evaporation rate (n-butylacetate = 100)
No data available

Other physical and chemical parameters
No data available.

Oxidizing properties
No data available

SECTION 10: Stability and reactivity

10.1. Reactivity
No data available.

10.2.Chemical stability
The product is stable under the conditions, noted in section 7 “Handling and storage”.

10.3.Possibility of hazardous reactions
None known.

10.4.Conditions to avoid
Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5.Incompatible materials
Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6.▼Hazardous decomposition products
Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1.Information on hazard classes as defined in Regulation (EC) No 1272/2008

▼Acute toxicity

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Test method:	OECD 403

Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (4 hours)
Result:	>5000 mg/m³

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Test method:	OECD 401
Species:	Rat
Route of exposure:	Oral
Test:	L D 50
Result:	>5000 mg/kg

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Test method:	OECD 402
Species:	Rabbit
Route of exposure:	D ermal
Test:	L D 50
Result:	>5000 mg/kg

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2.Information on other hazards

Long term effects

None known.

▼Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to he a l th.

Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Species:	Daphnia, Daphnia magna
Duration:	48 hours

Test:	EL0
Result:	1000 mg/L

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Species:	Fish, Oncorhynchus mykiss
Duration:	96 hours
Test:	LL0
Result:	1000 mg/L

Product/substance	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Species:	Algae, Pseudokirchneriella subcapitata
Duration:	72 hours
Test:	EL0
Result:	1000 mg/L

Product/substance	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics
Species:	Daphnia, Daphnia magna
Duration:	48 hours
Test:	EL0
Result:	1000 mg/L

Product/substance	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics
Species:	Fish, Oncorhynchus mykiss
Duration:	96 hours
Test:	LL0
Result:	1000 mg/L

Product/substance	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics
Species:	Algae, Pseudokirchneriella subcapitata
Duration:	72 hours
Test:	EL0
Result:	1000 mg/L

Toxic to aquatic life with long lasting effects.

12.2.Persistence and degradability

Product/substance	Hydrocarbons,C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
Result:	>60%
Conclusion:	Readily biodegradable
Test:	OECD 301 F

Product/substance	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics
Conclusion:	Readily biodegradable

12.3.Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4.Mobility in soil

No data available.

12.5.Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. ▼Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7.Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms .
This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. ▾Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)
HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 14 – Ecotoxic
Dispose of contents/container to an approved waste disposal plant.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

13 07 03* Other fuels (including mixtures)

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env* *	Other information:
ADR	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-ethylhexyl nitrate)	Transport hazard class: 9 Label: 9 Classification code: M6 	III	Yes	Limited quantities: 5 L Tunnel restriction code: (-) See below for additional information.
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-ethylhexyl nitrate)	Transport hazard class: 9 Label: 9 Classification code: M6 	III	Yes	Limited quantities: 5 L EmS: F-A S- F See below for additional information.
IATA	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-ethylhexyl nitrate)	Transport hazard class: 9 Label: 9 Classification code: M6 	III	Yes	See below for additional information.

*Packing group
** Environmental hazards

▾Additional information

This product is within scope of the regulations of transport of dangerous goods.

These substances when carried in single or combination packaging's containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR/IMDG/IATA provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2, 4.1.1.4 - 4.1.1.8 (ADR, IMDG) / 5.0.2.4.1, 5.0.2.6.1.1, 5.0.2.8 (IATA).
-
ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with tr a ns por t.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

14.6.Special precautions for user
Not applicable.

14.7.Maritime transport in bulk according to IMO instruments
No data available.

SECTION 15: Regulatory information

15.1.Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application
No special.

Demands for specific education
No specific requirements.

SEVESO - Categories / dangerous substances
E2 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 200 tonnes / (upper-tier): 500 tonnes

Additional information
Tactile warning.
If this product is sold in retail, it must be delivered with child-resistant fastening.

Sources
Control of Major Accident Hazards (COMAH) Regulations 2015.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2.Chemical safety assessment
No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3
EUH044, Risk of explosion if heated under confinement.
EUH066, Repeated exposure may cause skin dryness or cracking.
H302, Harmful if swallowed.
H304, May be fatal if swallowed and enters airways.
H312, Harmful in contact with skin.
H315, Causes skin irritation.
H319, Causes serious eye irritation.
H332, Harmful if inhaled.
H335, May cause respiratory irritation.
H400, Very toxic to aquatic life.
H410, Very toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

= Additives to petrol or diesel fuel

▼Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The safety data sheet is validated by

Product Safety Department

▼ Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en